



GE  
Lighting



PAR 36

FCX-Q650PAR36/7 120V

**41673**

---

## Product information

PAR lamps provide a robust and flexible design solution for a wide range of applications. Choice of PAR36, PAR46, PAR56 or PAR64

- 3000 K or 4200 K colour temperature
  - Choice of beam widths
  - Excellent colour rendering
  - High efficiency combined with low operating costs
  - Robust and reliable
  - UV control
  - Easy retrofit
  - Colour consistent throughout life
  - Colour blends with halogen and fluorescent
- 



## Product data

DUN Code	00043168416733
Bulb Shape	PAR
Bulb Diameter [mm]	114.3
Cap/Base	GY5.3
Nominal beam angle [°]	21
Gross weight per piece [g]	260
Maximum Overall Length [mm]	70
Net weight per piece [g]	258
Brand	General Electric (GE)

## Performance data

Nominal power [W]	360
Nominal lamp voltage [V]	82
Nominal correlated colour temperature (CCT) [K]	3350
Colour Rendering Index (CRI) [Ra]	100
Rated Life [h]	75
Ballast Required	Yes
Nominal center beam candlepower (CBCP) [cd]	24000
Coil type	CC-8
Energy efficiency class (EEC)	D
Weighted energy consumption [kWh/1000h]	692.4

## Logistic data

Pack Quantity	12
Pallet quantity EUR (PC)	432
Pallet quantity UK (PC)	576
Outer case size	313 x 211 x 226 (mm)
Layer quantity	144 EUR, 192 UK
Layer quantity EUR	144
Layer quantity UK	192
Product status	Available

## Application areas



Club and Disco

## Downloads & Links

[Go to the catalog site \(HTTP\)](#)

## Disclaimer

Special purpose lamp – Stage Studio. Not suitable for household illumination.