

JC, JCD, JCS & JCV

- Only for Use in Approved Enclosed Halogen Fixtures
- 2-Pin Prefocus Base - GY9.5

Watts	Ushio Ordering Code	Ushio Lamp Description	Dimensions mm			Filament Type	Approx Lumens lm	Color Temp K	Avg Life h	Burn Position	Bulb Finish	Fig No
			Dia (A)	MOL (B)	LCL (C)							
2-Pin Prefocus Base – GY9.5												
80	1000171	DDJ/DZZ, JC10V-80W*	11.5	51.0	27.0	CBar6	1700	3150	1000	BD/Hor	Clear	1
100	1000459	EYL, JC12V-100WC4	11.5	62.0	36.5	CBar6	2900	3300	50	BD/Hor	Clear	1
100	1000504	FDT, JC12V-100W	11.5	57.0	27.0	CBar6	2900	3300	50	BD/Hor	Clear	1
132	1000176	DDP, JC22V-132W*	13.5	57.0	33.4	CBar6	3900	3250	125	BD/Hor	Clear	1
150	1000309	EKL, JCD21V-150W*	11.5	51.0	27.0	CC-6	4650	3350	40	BD/Hor	Clear	1
150	1000503	FDS/DZE, JC24V-150W	14.0	57.2	33.4	CBar6	5000	3400	50	BD/Hor	Clear	1
250	1000245	DYG, JCD30V-250WS	19.9	63.5	36.5	CC-6	8000	3400	15	BD/Hor	Clear	1
300	1000886	JCD100V-300WC*	22.0	63.0	36.5	CC-6	7500	3200	150	BD/Hor	Clear	2
300	1000540	FKW, JCS120V-300WC/UA	23.0	90.4	46.5	C-13	7800	3200	200	Univ	Clear	3
420	1000304	EKB, JCD120V-420WC	22.0	63.0	36.5	CC-6	11000	3200	75	BD/Hor	Clear	2
500	1000629	FTK, JCD120V-500WCT	22.0	65.3	36.5	CC-6	13500	3100	200	BD/Hor	Clear	1
500	1000914	JCD240V-500WC	24.0	62.0	36.5	2CC-8	12500	3200	50	BD/Hor	Clear	4
500	1000285	EHA, JCS120V-500W	19.5	76.0	36.5	C-13D	—	3200	75	BD/Hor	Clear	5
500	1000603	FRG, JCS120V-500WC1	23.0	90.4	46.5	C-13D	13000	3200	150	Univ	Clear	3
575	1003326	JCS120V-575WC	25.0	90.0	46.5	8-C-13D	15500	3200	300	BD	Clear	3
575	1003327	JCS120V-575WX	25.0	90.0	46.5	8-C-13D	12000	3200	1500	BD	Clear	3
600	1000251	DYS/DYV/BHC, JCD120V-600WC	22.0	63.0	36.5	CC-6	17000	3200	75	BD/Hor	Clear	2
600	1000252	DYS-5, JCD125V-600WC	22.0	63.0	36.5	CC-6	13750	3200	75	BD/Hor	Clear	2
600	1000547	FMR, JCV120V-600WGY	17.0	88.9	50.8	CC-8	12500	3000	2000	BD/Hor	Clear	6
625	1000089	BVE, JCS120V-625W	19.5	89.0	44.5	C-13D	—	3350	75	BD/Hor	Clear	5
650	1000305	EKD, JCD120V-650WS	19.9	66.0	36.5	CC-6	20000	3400	25	BD/Hor	Clear	2
650	1000604	FRK, JCS120V-650WC/UA	22.5	90.4	46.5	C-13D	17500	3200	200	Univ	Clear	3
650	1000249	DYR/220V, JCD220V-650WC1	24.0	63.0	36.5	2CC-8	16500	3200	50	BD/Hor	Clear	4
650	1000250	DYR/240V, JCD240V-650WC2	24.0	63.0	36.5	2CC-8	16500	3200	50	BD/Hor	Clear	4
800	1000909	JCD120V-800WC	24.0	62.0	36.5	CC-6	19500	3200	75	BD/Hor	Clear	2
900	1000088	BVA, JCS120V-900W	23.0	95.0	44.5	C-13D	—	3300	75	BD/Hor	Clear	3

* Special Order Item

